

Product data sheet



Room controller display compact module 4-gang



Reference number

LS 5194 KRM TS D

Room controller display compact module 4-gang

for cover kit 4-gang, complete, ref.-no.: ..504 TSA .. in the LS range

can be extended by means of a room controller

extension module, ref.-no: LS 5178 TSEM

can be extended by means of a push-button extension module, ref.-no.: LS 509.. TSEM

recommended mounting height: 1.5 m

Intended use

- Measurement and feedback control of the room temperature
- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in wall box according to DIN 49073

Product characteristics

Each button can be used for push-button sensor of controller functions.

- Backlit LC display
 - One or two functions per button
 - To be completed with cover kit
 - Eight status LED – red, green or blue
 - Brightness of status LED and LCD adjustable
 - Integrated bus coupling unit
 - Connection of extension modules
 - Integrated room temperature sensor
 - External sensor (ref.-no.: FF 7.8) can be connected
 - Room temperature control with setpoint value specification
 - Two internal independent controllers for two independent areas – in connection with extension modules
 - Display of room or set temperature (°C or °F)
 - Display of outdoor temperature – with external sensor, e.g. weather station
 - Display of time, in conjunction with KNX time encoder
 - Push-button function or rocker function
 - Inhibit function: blocking or change of function of the entire or single button functions
 - Alarm function, optional with acknowledge by pressing any button
- Function symbols can be shown

Accessories:

external sensor ref.-no.: FF 7.8