

# Product data sheet



## Universal push-button module 2-gang



### Reference number

LS 5092 TSM

### Universal push-button module, 2-gang

including transparent cover ref.-no.: LS 50 NA  
for cover kit 2-gang, complete, ref.-no.: ..502 TSA .. in the LS range  
can be extended by means of a push-button extension module, ref.-no.: LS 509.. TSEM  
ETS product family: Push-button  
Product type: 2-gang push-button

### Intended use

- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in flush-box according to DIN 49073

### Product characteristics

- Push-button functions for switching, dimming, blinds control, valuator, light scenes, etc.
- One or two functions per button
- To be completed with cover kit
- Inscription field can be illuminated
- One status LED per button, red, green or blue, adjustable
- One operation LED as orientation light and programming status – red, green or blue, adjustable
- Brightness of status LED, operation LED and inscription field adjustable, can be changed during operation, e.g. during night times
- Measurement of room temperature
- Extension unit for room temperature controller
- Inhibit function: Inhibit or function mode change of single or all button functions
- Alarm function, optional acknowledge by pressing any button

- Energy saving mode
- Integrated bus coupling unit
- Connection for a push-button extension module, 1-4 gang
- Transparent cover kit (included) for temporary site use without design covers

**Spare part:**

transparent cover ref.-no.: LS 50 NA

**Accessories:**

Neutral cover ref.-no.: LS 50 NA W, LS 50 NA WW, LS 50 NA LG, LS 50 NA SW,  
AL 50 NA-L, ES 50 NA-L, AL 50 NA AN-L, ME 50 NA C-L, ME 50 NA AT-L, ME 50 NA D-L