

# Product data sheet



## Room controller display compact module 2-gang



### Reference number

LS 5192 KRM TS D

### Room controller display compact module 2-gang

for cover kit 2-gang, complete, ref.-no.: ..502 TSA .. in the LS range  
can be extended by means of a room controller extension module, ref.-no.: LS 5178 TSEM  
can be extended by means of a push-button extension module, ref.-no.: LS 509.. TSEM

recommended mounting height: 1.5 m

### Intended use

- Measurement and feedback control of the room temperature
- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in wall box according to DIN 49073

### Product characteristics

Each button can be used for push-button sensor of controller functions.

- Backlit LC display
- One or two functions per button
- To be completed with cover kit
- Eight status LED – red, green or blue
- Brightness of status LED and LCD adjustable
- Integrated bus coupling unit
- Connection of extension modules
- Integrated room temperature sensor
- External sensor (ref.-no.: FF 7.8) can be connected
- Room temperature control with setpoint value specification
- Two internal independent controllers for two independent areas – in connection with extension modules
- Display of room or set temperature (°C or °F)
- Display of outdoor temperature – with external sensor, e.g. weather station
- Display of time, in conjunction with KNX time encoder
- Push-button function or rocker function
- Inhibit function: blocking or change of function of the entire or single button functions
- Alarm function, optional with acknowledge by pressing any button

- Function symbols can be shown

### Accessories:

external sensor ref.-no.: FF 7.8