

Product data sheet



Centre plate with anti lock-out function and sensor connection



Reference number

LS 5232 S WW

Centre plate with anti lock-out function and sensor connection

for motor control inserts ref.-no.: 230 ME, 232 ME and 224 ME

for sensors ref.-no.: 32 SD and LA 90

for extension flex ref.-no.: 32 K

The centre plate with activated "anti lock-out function" assures, that nobody can be shut out by automatic blinds (e.g. wind, alarm, brightness sensor, timer). A blind/shutter position can be set. The blind/shutter will stop at the desired position.

Function

- Short touch: UPPER or LOWER touch area for adjusting the slats, blind/shutter will be moved for the period the push-button is held, stopping the continuous moving
- Longer touch: LOWER touch area for continuous move downwards
- Longer touch (> 4 sec.): FULL touch area for activating the storing mode, UPPER touch area for activating the "anti lock-out function" (illuminated LED)
- Short touch: UPPER touch area for deactivating the "anti lock-out function". After mains failures the anti lock-out function is also deactivated.

Sun protection: A sunlight sensor permits automatic lowering of the blind/shutter dependent on sunshine.

The potentiometer on the reverse side of the centre plate enables the setting of the brightness value between approx. 5,000 and approx. 80,000 lux. Factory setting: 15,000 lux

Duroplastic (scratch-proof) glossy

Colour:

white

Material:

duroplastic