

# Product data sheet



## Room controller display module 2-gang



### Reference number

RCD LS 4092 M

### Room controller display module 2-gang

can be extended by means of a push-button extension module, ref.-no.: 409.. TSEM

recommended mounting height: 1.5 m

### Intended use

- Operation of consumers, e.g. lights on/off, dimming, blinds/shutters up/down, brightness values, temperatures, storing and recalling of light scenes etc.
- Room temperature control
- Installation in mounting box according to DIN 49073

### Product characteristics

- Push-button functions for switching, dimming, blinds control, valuator, light scenes, etc.
  - Vertical and horizontal key/rocker functions
  - Two red LEDs per control key as status or operation indicators
  - Display of values and texts
  - Running text display for one or two messages with max. 14 characters
  - Integrated room temperature sensor
  - Room temperature control with setpoint value preset
  - Display of room temperature and setpoint temperature
  - Indication of outside temperature (only with external sensor)
  - Integrated bus coupling unit
  - In combination with Facility Pilot "Multi-Room Control": music play control, display of music titles, artists, etc.
  - Display unit for the KNX central alarm unit
  - Fan coil application with up to 8 fan speeds and auto function
  - OLED graphic display with high resolution
  - High contrast
  - Viewing angle 170° from each direction
  - Transparent cover kit (included) for temporary site use without design covers
- Connection for a push-button extension module, 1-4 gang