

## Description



- Multi-functional display with room thermostat
- Glass front in white or black
- Freely configurable for displaying and controlling functions e.g. light settings, sun protection systems
- Backlit display and integrated time switch
- For control and regulation of heating, fan coils, air conditioning systems
- Up to 7 different display pages
- Automatic summer/winter time adjustment with power reserve
- Controls up to 8 rooms via own temperature profiles
- Weekly time switch with 8 channels with up to 3 different statuses, e.g. for light, shutters, fans etc.
- 3 heating programs
- Alternative continuous or on/off control
- Operation modes: comfort, stand-by, temperature reduction at night, frost protection
- Weather data from Theben weather stations can be displayed
- Free choice of programming via the ETS without plug-in
- Installation in flush-mounted socket

## Technical data

Operating voltage KNX	Bus voltage, ≤15 mA (<25 mA without power supply)
Operating voltage	230 V AC
Frequency	50 Hz
Installation type	Flush-mounted wall installation
Type of connection	KNX bus terminal
Stand-by consumption	0,4 W
Power reserve	1,5 years
Display	Display with 132 x 72 points (8 lines with various functions) e.g. title, switching, dimming, blinds/shutters, % value, HVAC, counter value, temperature, 2-byte value, 8/16 bit counter value etc.
Display lighting	LCD with white backlighting, dimmable
Ambient temperature	+0 °C ... +45 °C
Type of protection	IP 20
Protection class	II according to EN 60 730-1

## Scale drawings

