# Push-in type jumper bar; insulated; 2-way; Nominal current 76 A

*Item No.: 2016-402*

*Push-in type jumper bar; insulated; 2-way; Nominal current 76 A*

## Marking

RoHS ✓
Compliant

## Business data

| | |
|---|---|
| *Supplier* | *WAGO* |
| *Item no.* | *2016-402* |
| *GTIN / EAN* | *4017332002509* |
| *Content* | *1* |
| *Order amount* | *25* |
| *Customer item number* | |

## Notes

## Technical data

*Miscellaneous*

| | |
|---|---|
| *Color* | *light gray* |
| *Rated voltage (III / 3) [V]* | *800 [V]* |
| *Rated current [A]* | *76 [A]* |
| *Rated current (Ex e II) [A]* | *65 [A]* |
| *Fire load [MJ]* | *0.019 [MJ]* |
| *Weight [g]* | *4.7 [g]* |

## Technical data

| | |
|---|---|
| *Width* | *21.4 mm / 0.843 Inch* |
| *Height* | *23 mm / 0.906 Inch* |
| *Depth* | *4.1 mm / 0.161 Inch* |

## Images & drawings

## Address

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Telefon: 0571/887-0
Fax: 0571/887-169
http://www.wago.com
© WAGO Kontakttechnik GmbH & Co. KG
Technische Änderungen und Irrtümer vorbehalten.